



# TECHNICAL DATA SHEET

# **RASCOtight Hydrophilic Gasket**

RASCOtight Hydrophilic Gasket are gaskets made from special acrylic polymers that swell upon contact with water.

#### USF

RASCOtight Hydrophilic Gasket are used to waterproof plastics or fibre-cement tie bolts.

### **FEATURES**

- swells upon contact with water
- reversible swelling
- very straightforward application



# TECHNICAL/PHYSICAL DATA

diameter 26 mm (for plastics tie bolts)	
diameter 43 mm (for fibre-cement tie bolts)	
yellow	
solid	
acrylic polymers	
none	
suitable for up to 1 bar	
12 months in original container, in dry conditions	
	diameter 43 mm (for fibre-cement tie bolts) yellow solid acrylic polymers none suitable for up to 1 bar

## **APPLICATION**

A hydrophilic gasket shall be fitted (at approx. mid-position) around each tie bolt during erection of the wall formwork. RASCOtight Hydrophilic Gasket serve to seal the joint between tie bolt and concrete. RASCOtight Hydrophilic Tie Bolt plugs shall be used to seal the inside of the tie bolts.

# **GENERAL GUIDELINE**

To prevent premature swelling, RASCOtight Hydrophilic Gasket shall be stored in dry conditions and shall not be exposed to the weather for a longer period prior to casting. The system is suitable for both plastics and fibre-cement tie bolts. Care shall be taken to ensure that the hydrophilic gaskets are not dislodged when pouring concrete for high walls.

### **SAFETY NOTICE**

No special provisions.

# SUPPLY/ADDITIVE

Item no.	Product	Container	Contents	
1107.2201.001	RASCOtight Hydrophilic Gasket 26 mm	pack	50 pcs	
1107.2202.001	RASCOtight Hydrophilic Gasket 43 mm	pack	50 pcs	

LEGAL NOTICE: The information provided on the use and application of our products in this technical Rascor International Ltd. data sheet is based on the present state of our knowledge. The customer shall bear sole Gewerbestrasse 4 responsibility for the proper specification, application and use of the products in line with the intended purpose, project-specific conditions and external actions. The most recent technical data sheet shall apply. The current technical data sheets are available at www.rascor.com. Our General Terms of Business shall form an integral part of this technical data sheet.

CH-8162 Steinmaur / Switzerland Phone: +41 (0)44 857 11 11 Fax: +41 (0)44 857 11 00 www.rascor.com