



rascor®

TECHNICAL DATA SHEET

RASCOflex AY-PE (Elastomer)

RASCOflex AY-PE Elastomer can be added to all RASCOflex AY injection grouts as a substitute for water.

USE

The elastomer is always used as a water substitute where the place of injection is likely to remain particularly dry for longer periods. Use of the elastomer significantly reduces shrinkage of the acrylic grout while considerably improving adhesion to the base.

FEATURES

- significant reduction in shrinkage
- improved adhesion to base
- must only be added to B component

CE



TECHNICAL/PHYSICAL DATA

Supplied form	liquid
Material colour	milky
Container type	canister
Container size	25 ltr
Density (DIN EN ISO 2811)	1,05 kg/ltr (± 0,05)
Hazardous goods/ADR	none
Application temperature	from +3° C to + 40° C
Storage/shelf life	12 months in original container, from +5° C to + 25° C, in dry conditions

APPLICATION

RASCOflex AY-PE shall always be added to the B component. Very thorough mixing with a mixing paddle is required after addition. Use of a drill with mixing paddle attachment is recommended. Under no circumstances shall the same mixing paddle be used for both A and B components.

GENERAL GUIDELINE

The use of different containers and mixing implements for the A and B components is essential. Prepared, but unused B component shall be clearly marked.

SAFETY NOTICE

Suitable protective clothing, gloves and goggles shall be worn. An eyewash bottle shall be kept at hand. For further details, please consult the safety data sheet.

SUPPLY/ADDITIVE

Item no.	Product	Container	Contents
1101.3041.001	RASCOflex AY-PE	canister	25 ltr

LEGAL NOTICE: The information provided on the use and application of our products in this technical data sheet is based on the present state of our knowledge. The customer shall bear sole responsibility for the proper specification, application and use of the products in line with the intended purpose, project-specific conditions and external actions. The most recent technical data sheet shall apply. The current technical data sheets are available at www.rascor.com. Our General Terms of Business shall form an integral part of this technical data sheet.

Rascor International Ltd.
Gewerbestrasse 4
CH-8162 Steinmaur / Switzerland
Phone: +41 (0)44 857 11 11
Fax: +41 (0)44 857 11 00
www.rascor.com