

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

RASCOflex PU118X LM B-Comp

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Rascor Construction Chemicals GmbH
Ratsgasse 6
97688 Bad Kissingen
Tel.: +49 (0) 971 130 2738
Fax: +49 (0) 971 133 6251

GB

Distributor:
Rascor International AG
Gewerbestr. 4
8162 Steinmaur
Tel.: +41 (0) 44-857 11 11
Fax: +41 (0) 44-857 11 00

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+41 (0) 44-857 11 11 (8.00h - 17.00h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 06.05.2021 / 0007

Valid from: 01.11.2021

PDF print date: 01.11.2021

RASCOflex PU118X LM B-Comp

Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H373-May cause damage to organs through prolonged or repeated exposure. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer.

P201-Obtain special instructions before use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing and eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P403+P233-Store in a well-ventilated place. Keep container tightly closed.

EUH204-Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

Diphenylmethanediisocyanate, isomeres and homologues

4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with butane-1,3-diol, 2,4'-diisocyanatodiphenylmethane, 2,2'-oxydiethanol and propane-1,2-diol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	9016-87-9
content %	10-30

Page 3 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0008
 Replacing version dated / version: 06.05.2021 / 0007
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 RASCOflex PU118X LM B-Comp

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 % Resp. Sens. 1, H334: >=0,1 % STOT SE 3, H335: >=5 %

4,4'-methylenediphenyl diisocyanate	
Registration number (REACH)	---
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	202-966-0
CAS	101-68-8
content %	10-30
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 % Resp. Sens. 1, H334: >=0,1 % STOT SE 3, H335: >=5 %

4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with butane-1,3-diol, 2,4'-diisocyanatodiphenylmethane, 2,2'-oxydiethanol and propane-1,2-diol	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	500-415-1
CAS	158885-29-1
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

Propylene carbonate	
Registration number (REACH)	---
Index	607-194-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-572-1
CAS	108-32-7
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Irrit. 2, H319

o-(p-isocyanatobenzyl)phenyl isocyanate	
Registration number (REACH)	---
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	227-534-9
CAS	5873-54-1
content %	1-10

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: ≥ 5 % Eye Irrit. 2, H319: ≥ 5 % Resp. Sens. 1, H334: $\geq 0,1$ % STOT SE 3, H335: ≥ 5 %

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

Watering eyes

Coughing

Irritation of the respiratory tract

Irritant to mucosa of the nose and throat

Respiratory distress

Oedema of the lungs

Headaches

Drying of the skin.

Dermatitis (skin inflammation)

Discoloration of the skin

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Hydrocyanic acid (hydrogen cyanide)

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Or:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Exposed employees should have regular medical check-ups.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Protect against moisture and store closed.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

Observe special requirements for isocyanates, also within the framework of the risk assessment and definition of protective measures.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues		
WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as - NCO))	WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as - NCO))	---	
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as - NCO))		
Chemical Name	4,4'-methylenediphenyl diisocyanate		
WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as - NCO))	WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as - NCO))	---	
Monitoring procedures:	ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2007 MDHS 25/4 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 2015 - EU project BC/CEN/ENTR/000/2002-16 card 7-4 (2004) - NIOSH 5521 (ISOCYANATES, MONOMERIC) - 1994 - NIOSH 5522 (ISOCYANATES) - 1998 - NIOSH 5525 (ISOCYANATES, TOTAL (MAP)) - 2003 - OSHA 18 (Diisocyanates 2,4-TDI and MDI) - 1980 - OSHA 47 (Methylene Bisphenyl Isocyanate (MDI)) - 1984		
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as - NCO))		
Chemical Name	4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with butane-1,3-diol, 2,4'-diisocyanatodiphenylmethane, 2,2'-oxydiethanol and propane-1,2-diol		
WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as - NCO))	WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as - NCO))	---	
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as - NCO))		
Chemical Name	o-(p-isocyanatobenzyl)phenyl isocyanate		
WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as - NCO))	WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as - NCO))	---	
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as - NCO))		
Chemical Name	1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich		
WEL-TWA: 5 mg/m ³ (DIDP, DINP)	WEL-STEL: ---	---	
Monitoring procedures: ---			
BMGV: ---	Other information: ---		

Diphenylmethanediisocyanate, isomeres and homologues

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg	
Consumer	Human - oral	Short term, local effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	

4,4'-methylenediphenyl diisocyanate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	

Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

Propylene carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sporadic (intermittent) release		PNEC	9	mg/l	
	Environment - marine		PNEC	0,09	mg/l	
	Environment - sediment, marine		PNEC	0,083	mg/l	
	Environment - soil		PNEC	0,81	mg/l	
	Environment - freshwater		PNEC	0,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,83	mg/l	
	Environment - sewage treatment plant		PNEC	7400	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	10	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	10	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,4	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	70,53	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	176	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	20	mg/m3	

o-(p-isocyanatobenzyl)phenyl isocyanate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - soil		PNEC	1	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg body weight/day	

Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg body weight/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	20,83	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,3	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,75	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	41,67	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5,29	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective gloves made of butyl (EN ISO 374).

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective PVC gloves (EN ISO 374).

Protective hand cream recommended.

The recommended maximum wearing time is 50% of breakthrough time.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown, Slightly
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	> 135 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.

pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	50 mPas (25°C, Dynamic viscosity)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	< 1 mbar (20°C)
Density and/or relative density:	1,12 g/cm ³ (25°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
9.2 Other information	
Explosives:	Product is not explosive.
Oxidising liquids:	There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.
 The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.
 Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.
 No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.
 Protect from humidity.

10.5 Incompatible materials

Amines
 Alcohols
 Bases
 Acids

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.
 See also section 5.2
 CO₂
 CO₂ formation in closed tanks causes pressure to rise.
 Pressure increase will result in danger of bursting.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

RASCOflex PU118X LM B-Comp						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	3,16-4,64	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.

Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Diphenylmethanediisocyanate, isomeres and homologues						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	0,49	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Respiratory or skin sensitisation:				Rat		Yes (inhalation)
Germ cell mutagenicity:				Salmonella typhimurium	Regulation (EC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)	Analogous conclusion, Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:		1	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Positive
Reproductive toxicity (Developmental toxicity):		4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity (Effects on fertility):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	NOAEL	12	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Aerosol
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEC	0,2	mg/kg		OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	
Aspiration hazard:						No

Symptoms:						fever, coughing, headaches, nausea and vomiting, dizziness, breathing difficulties, laryngeal oedema, abdominal pain, diarrhoea
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory organs, May cause respiratory irritation.

4,4'-methylenediphenyl diisocyanate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>2,24	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	0,368	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation)
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Limited evidence of a carcinogenic effect.

Symptoms:						respiratory distress, coughing, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract, Target organ(s): respiratory system

Propylene carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Human being		No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 482 (Gen. Tox. - DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Aspiration hazard:						No
Symptoms:						breathing difficulties, headaches, gastrointestinal disturbances, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	>5000	mg/kg		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOEC	100	mg/m3		OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Dust, Mist
---	------	-----	-------	--	--	------------

o-(p-isocyanatobenzyl)phenyl isocyanate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	0,387	mg/l/4h	Rat		Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (inhalation), Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Limited evidence of a carcinogenic effect.
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Symptoms:						asthmatic symptoms, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory tract, Irritant

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>0,13	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant

Page 16 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0008
 Replacing version dated / version: 06.05.2021 / 0007
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 RASCOflex PU118X LM B-Comp

Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:						No indications of such an effect.
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:						No indications of such an effect.
Symptoms:						headaches, fatigue, dizziness, nausea

11.2. Information on other hazards

RASCOflex PU118X LM B-Comp						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

RASCOflex PU118X LM B-Comp							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Diphenylmethanediisocyanate, isomeres and homologues							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>= 10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	

12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not biodegradable
12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other information:	BOD	28d	<10	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

4,4'-methylenediphenyl diisocyanate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC0	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion

12.1. Toxicity to algae:	EC50	72h	1,5	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide) ., According to experience available to date, polycarbamide is inert and non-degradable.
12.2. Persistence and degradability:	BOD	28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide) ., According to experience available to date, polycarbamide is inert and non-degradable.
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	Log Pow		4,51-5,22			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Toxicity to annelids:	EC50	14d	>= 1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Propylene carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Cyprinus caprio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>900	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			83,5-87-7	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable2 9d
12.2. Persistence and degradability:	DOC	14d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	
12.3. Bioaccumulative potential:	Log Pow		-0,41				Bioaccumulation is unlikely (LogPow < 1), calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	7400	mg/l	Pseudomonas putida	DIN 38412 T.8	

Page 20 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0008
 Replacing version dated / version: 06.05.2021 / 0007
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 RASCOflex PU118X LM B-Comp

Other information:	AOX		0	%			Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
--------------------	-----	--	---	---	--	--	---

o-(p-isocyanatobenzyl)phenyl isocyanate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	> 1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide) ., Analogous conclusion
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000		Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 21 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0008
 Replacing version dated / version: 06.05.2021 / 0007
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 RASCOflex PU118X LM B-Comp

12.1. Toxicity to fish:	LC0	96h	0,62	mg/l	Oncorhynchus mykiss	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,0034	mg/l	Daphnia magna	
12.1. Toxicity to algae:	NOEC/NOEL	8d	0,8	mg/l	Pseudokirchnerie lla subcapitata	
12.2. Persistence and degradability:		28d	67,1	%		Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		8,8			Slight
12.4. Mobility in soil:	Log Koc		5,46			
12.5. Results of PBT and vPvB assessment						No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable

Transport by sea (IMDG-code)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	Not applicable

Transport by air (IATA)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	

Page 22 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0008
 Replacing version dated / version: 06.05.2021 / 0007
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 RASCOflex PU118X LM B-Comp

Not applicable
 14.3. Transport hazard class(es): Not applicable
 14.4. Packing group: Not applicable
 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Regulation (EC) No 1907/2006, Annex XVII
 Diphenylmethanediisocyanate, isomeres and homologues
 4,4'-methylenediphenyl diisocyanate
 4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with butane-1,3-diol, 2,4'-diisocyanatodiphenylmethane, 2,2'-oxydiethanol and propane-1,2-diol
 o-(p-isocyanatobenzyl)phenyl isocyanate
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Acute Tox. — Acute toxicity - inhalation

STOT RE — Specific target organ toxicity - repeated exposure

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

Page 24 of 24
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0008
 Replacing version dated / version: 06.05.2021 / 0007
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 RASCOflex PU118X LM B-Comp

EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 TOC Total organic carbon
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
 No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.