



## INSTALLATION GUIDELINES

# RASCOTight Hydrophilic Tie Bolt Plug

### GENERAL

To seal tie bolts, a „Flupp“ plug is always needed in addition to the RASCOTight hydrophilic tie bolt plug. The RASCOTight hydrophilic tie bolt plug shall always be incorporated on the water (exposed) side.

RASCOTight hydrophilic gaskets are optionally available for 26 mm dia. PVC tie bolts or 43 mm dia. fibre-cement tie bolts.

The RASCOTight hydrophilic products shall be stored in dry conditions. RASCOTight hydrophilic gaskets shall be protected from water prior to casting.



### PERSONAL PROTECTIVE EQUIPMENT

- Wear suitable protective gloves and goggles




### INCORPORATION

- Concrete cover: 8 cm





### PROCEDURE (FROM WATER SIDE)

- Drive in „Flupp“ plug
- Press in hydrophilic tie bolt plug



- Optional incorporation of hydrophilic gasket



LEGAL NOTICE: The information provided on the use and application of our products in this technical data sheet is based on the present state of our knowledge. The customer shall bear sole responsibility for the proper specification, application and use of the products in line with the intended purpose, project-specific conditions and external actions. The most recent technical data sheet shall apply. The current technical data sheets are available at [www.rascor.com](http://www.rascor.com). Our General Terms of Business shall form an integral part of this technical data sheet.

**Rascor International Ltd.**  
**Gewerbestrasse 4**  
**CH-8162 Steinmaur / Switzerland**  
**Phone: +41 (0)44 857 11 11**  
**Fax: +41 (0)44 857 11 00**  
**[www.rascor.com](http://www.rascor.com)**