SAFETY DATA SHEET RASCOflex US509F B-Comp

According to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RASCOflex US509F B-Comp

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Semi-flexible silicate polyurethane Injection Resin

1.3. Details of the supplier of the safety data sheet

Supplier Rascor Construction Chemicals GmbH, Ratsgasse 6, 97688 Bad Kissingen, Germany

Phone: +49 (0) 971 130 2738, Fax: +49 (0) 971 133 6251

Rascor International AG, Gewerbestrasse 4, 8162 Steinmaur, Switzerland

Phone: +41 (0) 44-857 11 11, Fax: +41 (0) 44-857 11 00

1.4. Emergency telephone number

Emergency telephone Phone: +41 (0) 44-857 11 11 (8.00h - 17.00h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1

- H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards Not Classified

2.2. Label elements

Pictogram





Signal word Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

RASCOflex US509F B-Comp

Precautionary statements P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Contains 4,4'-methylenediphenyl diisocyanate, Isocyanic Acid, polymethylenepolyphenylene ester, o-(p-

isocyanatobenzyl)phenyl isocyanate

Supplementary precautionary

statements

P271 Use only outdoors or in a well-ventilated area.

P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

30-60%

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

4,4'-methylenediphenyl diisocyanate

CAS number: 101-68-8 FC number: 202-966-0

Classification

STOT SE 3 - H335 STOT RE 2 - H373 Resp. Sens. 1 - H334 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Skin Irrit. 2 - H315 Carc. 2 - H351

STOT SE 3 - H335

RASCOflex US509F B-Comp

Isocyanic Acid, polymethylenepolyphenylene ester

30-60%

CAS number: 9016-87-9

Classification

Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373

STOT SE 3 - H335

o-(p-isocyanatobenzyl)phenyl isocyanate

5-10%

CAS number: 5873-54-1 EC number: 227-534-9

Classification

Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Eye Irrit. 2 - H319 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 STOT RE 2 - H373 Carc. 2 - H351 STOT SE 3 - H335

STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Get medical attention. Treat symptomatically.

Inhalation IF INHALED: Get medical attention immediately. Move affected person to fresh air and keep

warm and at rest in a position comfortable for breathing. Do not induce vomiting.

Ingestion IF SWALLOWED: Get medical attention immediately. If throat irritation or coughing persists,

proceed as follows. Rinse mouth thoroughly with water. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Stop if the affected person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit

does not enter the lungs.

Skin contact IF ON SKIN (or hair): Rinse immediately with plenty of water. Continue to rinse for at least 10

minutes. Get medical attention if irritation persists after washing. Remove contaminated

clothing.

Eye contact IF IN EYES: Remove any contact lenses and open eyelids wide apart. Continue to rinse for at

least 15 minutes and get medical attention. Get medical attention if irritation persists after

washing.

Protection of first aidersFirst aid personnel should wear appropriate protective equipment during any rescue.

RASCOflex US509F B-Comp

4.2. Most important symptoms and effects, both acute and delayed

General informationTreat symptomatically. See Section 11 for additional information on health hazards.

Inhalation May cause sensitisation by inhalation. The liquid may be irritating to eyes, respiratory system

and skin. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Development of symptoms may be delayed for 24 to 48 hours.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact May cause skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Causes skin and eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water, if avoidable.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is not flammable. Irritating gases or vapours.

Hazardous combustion

products

Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Stop leak if safe to do so. If leakage cannot be stopped, evacuate area. Move containers from

fire area if it can be done without risk.

Special protective equipment

for firefighters

Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep

unnecessary and unprotected personnel away from the spillage. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Follow precautions for safe handling described in

this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the

Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

RASCOflex US509F B-Comp

Methods for cleaning up

If leakage cannot be stopped, evacuate area. Move containers from spillage area. Large Spillages: Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions For profession

For professional users only. Do not handle until all safety precautions have been read and understood. Use only in well-ventilated areas. Protect from moisture. Keep container dry. Container must be kept tightly closed when not in use. Do not eat, drink or smoke when using this product

this product.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Provide eyewash station. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at temperatures between 4°C and 30°C. Store in tightly-closed, original container in a

dry, cool and well-ventilated place. Do not store near heat sources or expose to high temperatures. Store away from the following materials: Acids. Protect from moisture.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Short-term exposure limit (15-minute): Isocyanic acid, polymethylenepolyphenylene ester EH40/2005 WEL's (United Kingdom (UK), 8/2007).

Skin sensitiser. 0.07 mg/m³ (as NCO)

Long-term exposure limit (8-hour TWA): 0.02 mg/m³ (as NCO)

Short-term exposure limit (15-minute): 4,4'-methylenediphenyl diisocyanate EH40/2005 WELs (United Kingdom (UK), 8/2007.

Skin sensitiser. 0.07 mg/m³ (as NCO)

Long-term exposure limit (8-hour TWA): 0.02 mg/m³ (as NCO)

Recommended monitoring procedures: Medical supervision of all employees who handle or come into contact with respiratory sensitisers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products. The Occupational Exposure Limits listed do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further exposure.

Isocyanic Acid, polymethylenepolyphenylene ester

Long-term exposure limit (8-hour TWA): EH40/2005 WELs (UK), 12/2011. Skin sensitiser 0.07 mg/m³, (as NCO) 8 hour(s). Short-term exposure limit (15-minute): EH40/2005 WELs (UK), 12/2011. Skin sensitiser 0.07 mg/m³, (as NCO)

RASCOflex US509F B-Comp

DNEL Diphenylmethane 4,4'-diisocyanate

Workers - Dermal; Short term systemic effects: 50 mg/kg bw/day Workers - Inhalation; Short term systemic effects: 0.1 mg/m³ Workers - Inhalation; Short term local effects: 0.1 mg/m³ Workers - Inhalation; Long term systemic effects: 0.05 mg/m³ Workers - Inhalation; Long term local effects: 0.05 mg/m³

Consumer - Dermal; Short term systemic effects: 25 mg/kg bw/day Consumer - Inhalation; Short term systemic effects: 0.05 mg/m³ Consumer - Oral; Short term systemic effects: 20 mg/kg bw/day Consumer - Dermal; Short term local effects: 17.2 mg/cm² Consumer - Inhalation; Short term local effects: 0.05 mg/m³ Consumer - Inhalation; Long term systemic effects: 0.025 mg/m³ Consumer - Inhalation; Long term local effects: 0.025 mg/m³

PNEC Industry/Professional - Fresh water; 1 mg/l

- Marine; 0.1 mg/l- Soil; 1 mg/kg- STP; 1 mg/l

Isocyanic Acid, polymethylenepolyphenylene ester (CAS: 9016-87-9)

DNEL Workers - Dermal; Short term systemic effects: 50 mg/kg

Consumer - Dermal; Short term systemic effects: 25 mg/kg Consumer - Inhalation; Short term systemic effects: 0.05 mg/m³ Consumer - Oral; Short term systemic effects: 20 mg/kg/day Consumer - Dermal; Short term local effects: 17.2 mg/cm² Consumer - Inhalation; Long term systemic effects: 0.025 mg/m³

Workers - Inhalation; Short term local effects: 0.1 mg/m³
Workers - Dermal; Short term local effects: 28.7 mg/cm²
Workers - Inhalation; Short term systemic effects: 0.1 mg/m³
Workers - Inhalation; Long term systemic effects: 0.05 mg/m³
Workers - Inhalation; Long term local effects: 0.05 mg/m³
Consumer - Inhalation; Short term local effects: 0.05 mg/m³
Consumer - Inhalation; Long term local effects: 0.025 mg/m³

PNEC - Fresh water; 1 mg/l

- Marine water; 0.1 mg/l

- Soil; 1 mg/kg - STP; 1 mg/l

- Intermittent release; 10 mg/l

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

This product is not to be used under conditions of poor ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/face protection

Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. It is recommended that gloves are made of the following material: Nitrile rubber. Butyl rubber.

RASCOflex US509F B-Comp

Other skin and body

protection

controls

Wear appropriate clothing to prevent skin contamination.

Hygiene measures Wash hands thoroughly after handling. Promptly remove any clothing that becomes

contaminated. Do not eat, drink or smoke when using this product.

Respiratory protection Combination filter, type A2/P3.

Environmental exposure

Keep container tightly sealed when not in use. Residues and empty containers should be

taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Coloured liquid.

Colour Brown.

Odour Characteristic.

Odour threshold Not determined.

PH Not determined.

Melting point Not applicable.

Initial boiling point and range 245°C

Flash point 230°C CC (Closed cup).

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Not applicable.

Other flammability Not applicable. Vapour pressure Not determined. Not determined. Vapour density **Bulk density** Not applicable. Solubility(ies) Not determined. Partition coefficient Not determined. Auto-ignition temperature Not determined. Not determined. **Decomposition Temperature**

Viscosity 150-250 mPa s @ 25°C

Explosive properties Not applicable.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not applicable.

Density 1.24 kg/lt @ 23°C

9.2. Other information

RASCOflex US509F B-Comp

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Water-reactive materials.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

The following materials may react with the product: Water, moisture.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong alkalis. Amines. Alcohols.

10.6. Hazardous decomposition products

Hazardous decomposition Heating may generate the following products: Hydrogen cyanide (HCN). Carbon dioxide

products (CO2). Carbon monoxide (CO). Nitrous gases (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 10000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ 9400 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ 0.49 mg/m³, Inhalation, Rat

ATE inhalation (gases ppm) 90,000.0

ATE inhalation (vapours mg/l) 11.0

ATE inhalation (dusts/mists 30.0

mg/l)

Skin corrosion/irritation

Animal data Isocyanic acid, polymethylenepolyphenylene ester

Test - OECD 404 Acute Dermal Irritation/Corrosion

Species - Rabbit

Route of Exposure - Skin Result - Mild irritant

Respiratory sensitisation

RASCOflex US509F B-Comp

Respiratory sensitisation Isocyanic acid, polymethylenepolyphenylene ester:

Test - No official guidelines Route of exposure - Respiratory

Species - Guinea pig

Result - Sensitising 4,4'-Methylenediphenyl diisocyanate:

Test - No official guidelines Route of exposure - Respiratory

Species - Guinea pig Result - Sensitising

Skin sensitisation

Skin sensitisation Isocyanic acid, polymethylenepolyphenylene ester:

Route of exposure - Skin

Species - Mouse

Result - Sensitising 4,4'-Methylenediphenyl diisocyanate:

Route of exposure - Skin

Species - Mouse Result - Sensitising

Carcinogenicity

Carcinogenicity Isocyanic acid, polymethylenepolyphenylene ester Carcinogenicity Studies EU 2 Jahre 5 Tage

pro Woche , Inhalation, Rat Result - Negative OECD 453 Combined Chronic Toxicity, Carcinogenicity Studies EU 2 Jahre 5 Tage pro Woche , Inhalation, Rat Result - Positive Target organs - lungs Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in chronic pulomonary irritation at high concentrations. Only at the top level (6 mg/m3), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adencarcinoma). There were no lung tumours at 1 mg/m3 and no effects at 0.2 mg/m3. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occured throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and

lung damage, it is highly unlikely that tumour formation will occur.

IARC carcinogenicity Isocyanic acid, polymethylenepolyphenylene ester - 3

4,4'-Methylenediphenyl diisocyanate - 3

Reproductive toxicity

Reproductive toxicity - development

4,4'-Methylenediphenyl diisocyanate Does not contain any substances known to be toxic to

reproduction. No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

irritation 4,4'-Methylenediphenyl diisocyanate

Specific target organ toxicity - repeated exposure

4,4'-Methylenediphenyl diisocyanate Category 2 - Inhalation - Respiratory tract

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

9/13

RASCOflex US509F B-Comp

General information Mutagenicity:

Isocyanic acid, polymethylenepolyphenylene ester

Test - OECD 474 Result - Negative

Equivocal Product/ingredient name - 4,4'-Methylenediphenyl diisocyanate Test - EU EC B. 13/14 Mutagenicity -Reverse Mutation Testing using Bacteria

Result - Negative

Test - OECD 474 Mammalian Erythrocyte Micronucleus Test

Result - Negative No specific health hazards known.

Skin contact The liquid may be irritating to skin.

Eye contact The product is irritating to eyes and skin.

Acute and chronic health

Potential chronic health effects:

hazards

Isocyanic acid, polymethylenepolyphenylene ester

Test - OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies

Result type - NOEC Dusts and mists

Result - 0.2 mg/m3 This product may cause skin and eye irritation. May cause damage to

mucous membranes in nose, throat, lungs and bronchial system.

Route of entry Inhalation Ingestion Skin and/or eye contact

Medical symptoms Symptoms following overexposure may include the following: Allergic rash. Asthma,

pulmonary sensitisation. Breathlessness. Coughing, chest tightness, feeling of chest pressure.

SECTION 12: Ecological Information

12.1. Toxicity

Acute toxicity - fish Isocyanic acid, polymethylenepolyphenylene ester

LC₅₀, 96 hours: >1000 mg/l, Fish

No official guidelines Chronic NOEC, 112 days: >10000 mg/kg, Fish

4,4'-Methylenediphenyl diisocyanate LC₅o, 96 hours: >1000 mg/l, Fish

Acute toxicity - aquatic

Isocyanic acid, polymethylenepolyphenylene ester

invertebrates

OECD 202 Daphnia sp. Acute Immobilisation Test* Acute EC50, 24 hours: >1000 mg/l,

Daphnia magna

NOEC, 112 days: >10000 mg/l, Daphnia magna

OECD 211 Daphnia Magna Reproduction Test, 21 days: >10 mg/l, Daphnia magna OECD 202 Daphnia sp. Acute Immobilisation Test* Acute EC50, 24 hours: >1000 mg/l,

Daphnia

Acute toxicity - aquatic plants

OECD 201 Alga, Growth Inhibition Test, 72 hours: >1640 mg/l, Algae No official guidelines Chronic NOEC, 112 days: >10000 mg/l, Algae

Acute toxicity - microorganisms

OECD 209 Activated Sludge, Respiration Inhibition Test, 3 hours: >100 mg/l, Bacteria

12.2. Persistence and degradability

Modified MITI Test (II) - 28 days - 0% 4,4'-Methylenediphenyl diisocyanate OECD 302C

Inherent Biodegradability: Modified MITI Test (II) - 28 days - 0%

Biodegradation Isocyanic acid, polymethylenepolyphenylene ester

Not readily biodegradable.

4,4'-Methylenediphenyl diisocyanate

Not readily biodegradable.

RASCOflex US509F B-Comp

12.3. Bioaccumulative potential

Bioaccumulative potential Isocyanic acid, polymethylenepolyphenylene ester log Pow: BCF - 200 Potenzial - hoch, 4,4'-

Methylenediphenyl diisocyanate log Pow: 4.51 BCF - 200 Potenzial - hoch,

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility By considering the production and use of the substance, it is unlikely that significant

environmental exposure in the air or water will arise. Immiscible with water, but will react with water to produce inert and non-biodegradable solids. Conversion to soluble products, including diamino-diphenylmethane (MDA), is very low under the optimal laboratory conditions of good dispersion and low concentration. In air, the predominant degradation process is predicted to be a relativley rapid OH radical attacke, by calculation and by analogy with

related diisocyanates.

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Waste is classified as hazardous waste.

Disposal methodsDispose of contents/container in accordance with national regulations. Waste is classified as

hazardous waste.

Waste class European Waste Catalogue (EWC):

Waste Code - 08 05 01* Waste Designation - waste isocyanates

Waste Code - 16 03 05* Waste Designation - organic wastes containing dangerous

substances

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

RASCOflex US509F B-Comp

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

EH40/2005 Workplace exposure limits.

Health and Safety at Work etc. Act 1974 (as amended).

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list

of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and

Directive 91/689/EEC on hazardous waste with amendments.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

work (as amended).

Commission Regulation (EU) No 453/2010 of 20 May 2010.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Verwaltungsvorschrift wassergefährdende Stoffe (Germany): WGK 1 (slightly water pollutant)

Guidance Isocyanates: Health hazards and precautionary measures EH16.

Workplace Exposure Limits EH40.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

RASCOflex US509F B-Comp

SECTION 16: Other information

General information Only trained personnel should use this material.

Revision date 02/09/2015

Revision 1

SDS number 5131

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.