



TECHNICAL DATA SHEET

RASCOhybrid HMS317 AC (Accelerator)

RASCOhybrid HMS317 AC is an ancillary product for use with the RASCOhybrid HMS system.

USE

RASCOhybrid HMS317 AC is used whenever the standard gel time of the injection resin needs to be shortened. This can also serve to counteract slower gel times caused by lower temperatures.

FEATURES

- purpose-developed for RASCOhybrid HMS317 system
- gel time very closely controllable
- maximum proportion 20% (by volume)
- can be added directly on site
- guarantees fast homogenization



TECHNICAL / PHYSICAL DATA

Supplied form	liquid
Material colour	transparent
Container type	canister
Container size	4,8 ltr/5 kg
Hazardous goods/ADR	none
Application temperature	See technical data sheet for relevant RASCOhybrid HMS317 system
Storage/shelf life	12 months in original container, from +5° C to +25° C, in dark location

APPLICATION

RASCOhybrid HMS317 AC shall always be added to the A-component of the polyurethane mix. A maximum proportion of 20% (by volume) is recommended. Quantities exceeding this may have a negative impact on the end product. Very thorough mixing is required after addition of the accelerator. Use of a drill with mixing paddle is recommended.

The action of RASCOhybrid HMS317 AC is temperature-dependent and shall be determined for each specific application on the basis of preliminary tests. In addition to the ambient and material temperature, attention shall also be paid to the building fabric temperature.

GENERAL GUIDELINES

Unused accelerated A-components shall be clearly marked with precise details of the proportions added.

SAFETY NOTICE

Suitable protective clothing, gloves and goggles shall be worn. An eyewash bottle shall be kept at hand.

SUPPLY / ADDITIVES

Item No.	Product	Container	Contents
1113.3901.001	RASCOhybrid HMS317 AC	canister	4,8 ltr
1113.3901.002	RASCOhybrid HMS317 AC	canister	19,2 ltr

LEGAL NOTICE: The information provided on the use and application of our products in this technical data sheet is based on the present state of our knowledge. The customer shall bear sole responsibility for the proper specification, application and use of the products in line with the intended purpose, project-specific conditions and external actions. The most recent technical data sheet shall apply. The current technical data sheets are available at www.rascor.com. Our General Terms of Business shall form an integral part of this technical data sheet.

Rascor International Ltd.
Gewerbestrasse 4
CH-8162 Steinmaur / Switzerland
Phone: +41 (0)44 857 11 11
Fax: +41 (0)44 857 11 00
www.rascor.com