

RASCObond fixing adhesive

ADHESIVE SYSTEMS

ADHESIVE SYSTEMS

RASCObond adhesive systems primarily serve as an aid in applying and fixing other RASCOR waterproofing products or strips/sections. They excel, in particular, by their high adhesive strength. The specific applications of the individual RASCObond adhesive systems in some cases vary considerably.

USE

RASCObond fixing adhesive is a solvent-free, 1-component, silane-polymer-based adhesive. It is above all used for installing RASCOTight hydrophilic strip in joints. Although RASCObond fixing adhesive also adheres to damp substrates, the base should, if possible, be dry so as to achieve the maximum adhesive strength.

FEATURES

- bonds well to concrete, metal and plastics
- very straightforward application



Further product info



LEGAL NOTICE: The information provided on the use and application of our products in this technical data sheet is based on the present state of our knowledge. The customer shall bear sole responsibility for the proper specification, application and use of the products in line with the intended purpose, project-specific conditions and external actions. The most recent technical data sheet shall apply. The current technical data sheets are available at www.rascor.com. Our General Terms of Business shall form an integral part of this technical data sheet.

Rascor International Ltd.

Gewerbestrasse 4
CH-8162 Steinmaur / Switzerland
Phone: +41 (0)44 857 11 11
www.rascor.com
info@rascor.com

RASCOR Construction Chemicals GmbH

Ratsgasse 6
D-97688 Bad Kissingen / Germany
Phone: +49 (0)971 130 27 38
www.rascor.com
badkissingen@rascor.com

RASCObond fixing adhesive

ADHESIVE SYSTEMS

TECHNICAL / PHYSICAL DATA

Supplied form	paste, sag-resistant
Material colour	black
Container type	cartridge
Container size	310 ml
Density (DIN EN ISO 2811)	approx. 1.40 g/ml
Hazardous goods/ADR	none
Application temperature	from +5° C to +45° C
Storage/shelf life	12 months in original container, in dry conditions

SUPPLY / ADDITIVES

Item no.	Product	Container	Contents
1109.2101.002	RASCObond fixing adhesive	cartridge	1 pcs.

APPLICATION / PREPARATION

The base must be dry and free from dirt, dust, oil, grease and loose particles. RASCObond fixing adhesive is applied continuously using a standard extrusion gun, such as that used for mastics, to form a uniform bead. In case of rough bases, the bead must be large enough to fully even out the irregularities and ensure full contact between the RASCObond fixing adhesive and the subsequently installed hydrophilic strip. The cartridge should be moved across the base at an angle of at least 45° so as to ensure that the fixing adhesive is applied to the base with sufficient pressure.

One cartridge suffices to install approx. 7 m of hydrophilic strip. The exact consumption depends on the roughness of the base and may therefore vary significantly.

GENERAL GUIDELINES / SAFETY NOTICE

The cartridge should be moved across the base at an angle of at least 45° so as to ensure that the fixing adhesive is applied to the base with sufficient pressure.

